

### EARTH BONDING POINT

Earth Bonding Points are used for proving earthing continuity and a multiple bonding point, these bonding points are available with one, two and four hole connections. When cast into concrete they connect the re-bar to the main earthing or lightning protection system. These are also available with variety of tail lengths to suit deferent applications the tail ends are of 70 mm<sup>2</sup> yellow green pvc coated stranded cable which are pre welded by exothermic welding method.

Body - Gunmetal, Bolts - Al Bronze, Phosphor Bronze and SS  
BS EN 50164-1:2000 (8 Nm.)



### BONDING POINT

| Product Ref. | No. of Holes | L  | W  |
|--------------|--------------|----|----|
| BP1          | 1            | 77 | 49 |
| BP2          | 2            | 71 | 69 |
| BP4          | 3            | 80 | 63 |

### BONDING POINT WITH TAIL

| Product Ref. | No. of Holes | L  | W  | T    |
|--------------|--------------|----|----|------|
| BP150        | 1            | 76 | 40 | 500  |
| BP250        | 2            | 76 | 79 | 500  |
| BP2100       |              | 76 | 79 | 1000 |
| BP210        |              | 76 | 79 | 1500 |
| BP2300       |              | 76 | 79 | 3000 |
| BP450        | 4            | 80 | 64 | 500  |
| BP4100       |              | 80 | 64 | 1000 |
| BP4300       |              | 80 | 64 | 3000 |

### BONDING POINT WITH TAPE

| Product Ref. | No. of Holes | L  | W  | T    |
|--------------|--------------|----|----|------|
| BPT          | 2            | 82 | 54 | -    |
| BPT250       |              | 82 | 54 | 500  |
| BPT2100      |              | 82 | 54 | 1000 |
| BPT2150      |              | 82 | 54 | 1500 |
| BPT2300      |              | 82 | 54 | 3000 |