



Male Fully Insulating Joint



Model Number	Socket Specification	Dimension(mm)						Applicable Wire Range	Description
		W	F	L	B	D ϕ	C ϕ		
VMD - 1.25 - 250	0.8×6.35	6.35	7.3	23.0	12.0	4.5	2.3	22~16A.W.G 0.5~1.5mm ²	Material: Copper Maximum current: I _{max} = 10A
VMD - 2 - 250	0.8×6.35	6.35	7.7	24.0	11.0	4.5	2.3	16~14A.W.G 1.5~2.5mm ²	Material: Copper Maximum current: I _{max} = 15A
VMD - 5.5 - 250	0.8×6.35	6.35	7.7	25.0	13.0	6.3	3.4	12~10A.W.G 4~6mm ²	Material: Copper Maximum current: I _{max} = 24A

Female Fully Insulating Joint



Model Number	Socket Specification	Dimension(mm)						Applicable Wire Range	Description
		W	F	L	B	D ϕ	C ϕ		
VFD 1 - 47	0.5×4.75 0.8×4.75	5	6.5	20.2	11	4.0	1.7	22~16A.W.G 0.5~1.5mm ²	Material: Copper Maximum current: I _{max} = 10A
VFD 1.25-250	0.8×6.35								
VFD 2 - 47	0.5×4.75 0.8×4.75	5	6.5	20.2	11	4.5	2.3	16~14A.W.G 1.5~2.5mm ²	Material: Copper Maximum current: I _{max} = 15A
VFD 2-250	0.8×6.35								
VFD 5.5-250	0.8×6.35	6.6	7.3	24.0	13	6.3	3.4	12~10A.W.G 4~6mm ²	Material: Copper Maximum current: I _{max} = 24A