



Long-wide Insulation In The Middle Connector



ITEM NO	CABLE RANGE		Dimension (mm)			Description
	A.W.G	mm ²	L	dφ	D	
VNYF 1.25	22-16	0.5-1.5	27.3	1.7	3.2	19A
VNYF 2	16-14	1.5-2.5	27.3	2.3	3.4	27A
VNYF 5.5	12-10	4-6	27.3	3.4	3.8	48A

Soft Insulated Casing



ITEM NO	Dimension (mm)				
	D1	D2	D3	L	F
VSC 1.25	2.8	3.3	3.1	13.0	7.0
VSC 2	3.3	4.5	3.7	15.0	7.0
VSC 3.5	4.2	5.7	4.1	20.0	8.0
VSC 5.5	4.8	5.7	5.2	20.0	8.0
VSC 8	6.2	7.2	6.2	20.0	9.0
VSC 14	7.5	10.0	8.0	27.0	11.0
VSC 22	10.5	12.0	9.5	30.0	15.0
VSC 38	12.5	14.0	11.8	36.0	16.5
VSC 60	15.0	16.8	13.5	39.0	19.0
VSC 70	16.0	17.5	14.5	43.0	20.0
VSC 80	17.0	19.0	16.0	47.0	22.0
VSC 100	19.0	22.0	18.0	54.0	24.0
VSC 125	21.0	24.0	20.0	57.0	25.0
VSC 150	23.0	24.5	22.0	65.0	30.0
VSC 200	27.0	32.0	24.0	65.0	30.0
VSC 240	29.0	38.0	26.5	77.0	39.0
VSC 325	29.0	38.0	29.0	77.0	40.0
VSC 400	42.0	45.0	36.0	85.0	41.0
VSC 500	46.0	48.0	40.0	88.0	42.0
VSC 630	52.0	54.0	44.0	92.0	47.0