

WIRING DEVICES & ACCESSORIES

10A WALL SWITCH 1 WAY



SN 301



SN 303



SN 305



SN 307 X



SN 309



SN 316

MODEL NO.	MODEL	AMPERE RATING (A)	POWER (W)	STANDARD	MEASUREMENT / UNIT	CTN PACKING
SN 301	1 GANG 1 WAY	10	2500 W	BS EN 60669-1	86 X 86 MM	100 / CARTON
SN 303	2 GANG 1 WAY	10	2500 W	BS EN 60669-1	86 X 86 MM	100 / CARTON
SN 305	3 GANG 1 WAY	10	2500 W	BS EN 60669-1	86 X 86 MM	100 / CARTON
SN 307 X	4 GANG 1 WAY	10	2500 W	BS EN 60669-1	86 X 86 MM	100 / CARTON
SN 309	6 GANG 1 WAY	10	2500 W	BS EN 60669-1	86 X 146 MM	50 / CARTON
SN 316	1 GANG BELL PUSH	10	2500 W	BS EN 60669-1	86 X 86 MM	100 / CARTON

APPLICABLE WIRE RANGES	L,N,E
10A SWITCH	1.0 mm ² - 4.0 MM ²

INSULATION STRIPPING GAUGE	L,N	E
10A SWITCH	8 mm	8 mm

APPROPRIATE TIGHTENING TORQUE	L,N	E
10A SWITCH	0.6Nm-2.0Nm	1.6Nm-2.0Nm

VOLTAGE RATING	250 V~
MATERIAL	UREA
CONDUCTING STRIP & CLIP	BRASS & COPPER
CONTACTS	SILVER
MOUNTING DEPTH	10 mm

1 WAY SWITCH

