

Corugated Polyamide and Corugated Split Polyamide Conduit

Series Code ZM.13

Features Corugated , Polyamide PA6, halogen-free and non-flame propagating .

Product Photo



Item Code (Black)	Item Code (Grey)	Nom . Size	ID (mm)	OD (mm)	Packed (m)
ZM.13.1001	ZM.13.2001	7	6,5	10	100
ZM.13.1002	ZM.13.2002	8	8,5	12	100
ZM.13.1003	ZM.13.2003	9	10	13	100
ZM.13.1004	ZM.13.2004	11	12	15,8	50
ZM.13.1005	ZM.13.2005	13	14,2	18,4	50
ZM.13.1006	ZM.13.2006	16	16,5	21,2	50
ZM.13.1007	ZM.13.2007	21	23,5	28,4	50
ZM.13.1008	ZM.13.2008	29	29	34,5	25
ZM.13.1009	ZM.13.2009	36	36	42,5	25
ZM.13.1010	ZM.13.2010	48	48	54,5	25

Temperature Range -40°C~+120°C

IP Rating IP 68

Flexibility Highly flexible

Certificate CE

Profile



Series Code ZM.13

Features Corugated Split , Polyamide PA6, halogen-free and non-flame propagating .

Product Photo



Item Code (Black)	Item Code (Grey)	Nom . Size	ID (mm)	OD (mm)	Packed (m)
ZM.13.3001	ZM.13.4001	7	6,5	10	100
ZM.13.3002	ZM.13.4002	8	8,5	12	100
ZM.13.3003	ZM.13.4003	9	10	13	100
ZM.13.3004	ZM.13.4004	11	12	15,8	50
ZM.13.3005	ZM.13.4005	13	14,2	18,4	50
ZM.13.3006	ZM.13.4006	16	16,5	21,2	50
ZM.13.3007	ZM.13.4007	21	23,5	28,4	50
ZM.13.3008	ZM.13.4008	22	22	27,5	50
ZM.13.3009	ZM.13.4009	29	29	34,5	25
ZM.13.3010	ZM.13.4010	36	36	42,5	25

Temperature Range -40°C~+120°C

IP Rating IP 68

Flexibility Highly flexible

Certificate CE

Profile



Corrugated Polypropylene and Corrugated Split Polypropylene Conduit

Series Code ZM.13

Features Corrugated , Polypropylene.

Product Photo



Item Code (Black)	Item Code (Grey)	Nom. Size	ID (mm)	OD (mm)	Packed (m)
ZM.14.1001	ZM.14.2001	7	6,5	10	100
ZM.14.1002	ZM.14.2002	8	8,5	12	100
ZM.14.1003	ZM.14.2003	9	10	13	100
ZM.14.1004	ZM.14.2004	11	12	15,8	50
ZM.14.1005	ZM.14.2005	13	14,2	18,4	50
ZM.14.1006	ZM.14.2006	16	16,5	21,2	50
ZM.14.1007	ZM.14.2007	22	23,5	28,4	50
ZM.14.1008	ZM.14.2008	29	29	34,5	25
ZM.14.1009	ZM.14.2009	36	36	42,5	25
ZM.14.1010	ZM.14.2010	48	48	54,5	25

**Temperature
Range**

-40°C~+120°C

Flexibility

Highly flexible

Certificate

CE

Profile



Series Code ZM.13

Features Corrugated Split , Polypropylene.

Product Photo



Item Code (Black)	Item Code (Grey)	Nom. Size	ID (mm)	OD (mm)	Packed (m)
ZM.14.3001	ZM.14.4001	7	6,5	10	100
ZM.14.3002	ZM.14.4002	8	8,5	12	100
ZM.14.3003	ZM.14.4003	9	10	13	100
ZM.14.3004	ZM.14.4004	11	12	15,8	50
ZM.14.3005	ZM.14.4005	13	14,2	18,4	50
ZM.14.3006	ZM.14.4006	16	16,5	21,2	50
ZM.14.3007	ZM.14.4007	22	23,5	28,4	50
ZM.14.3008	ZM.14.4008	29	29	34,5	25
ZM.14.3009	ZM.14.4009	36	36	42,5	25
ZM.14.3010	ZM.14.4010	48	48	54,5	25

**Temperature
Range**

-40°C~+120°C

Flexibility

Highly flexible

Certificate

CE

Profile



Corugated Polypropylene and Corugated Split Polypropylene Conduit (Halogen Free)

Series Code ZM.13

Features Corugated , Polypropylene, halogen-free and non-flame propagating .

Product Photo



Item Code (Black)	Item Code (Grey)	Nom. Size	ID (mm)	OD (mm)	Packed (m)
ZM.14.5001	ZM.14.6001	7	6,5	10	100
ZM.14.5002	ZM.14.6002	8	8,5	12	100
ZM.14.5003	ZM.14.6003	9	10	13	100
ZM.14.5004	ZM.14.6004	11	12	15,8	50
ZM.14.5005	ZM.14.6005	13	14,2	18,4	50
ZM.14.5006	ZM.14.6006	16	16,5	21,2	50
ZM.14.5007	ZM.14.6007	22	23,5	28,4	50
ZM.14.5008	ZM.14.6008	29	29	34,5	25
ZM.14.5009	ZM.14.6009	36	36	42,5	25
ZM.14.5010	ZM.14.6010	48	48	54,5	25

Temperature Range

-40°C~+120°C

Flexibility

Highly flexible

Certificate

CE

Profile



Series Code ZM.13

Features Corugated Split , Polypropylene, halogen-free and non-flame propagating .

Product Photo



Item Code (Black)	Item Code (Grey)	Nom. Size	ID (mm)	OD (mm)	Packed (m)
ZM.14.7001	ZM.14.8001	7	6,5	10	100
ZM.14.7002	ZM.14.8002	8	8,5	12	100
ZM.14.7003	ZM.14.8003	9	10	13	100
ZM.14.7004	ZM.14.8004	11	12	15,8	50
ZM.14.7005	ZM.14.8005	13	14,2	18,4	50
ZM.14.7006	ZM.14.8006	16	16,5	21,2	50
ZM.14.7007	ZM.14.8007	22	23,5	28,4	50
ZM.14.7008	ZM.14.8008	29	29	34,5	25
ZM.14.7009	ZM.14.8009	36	36	42,5	25
ZM.14.7010	ZM.14.8010	48	48	54,5	25

Temperature Range

-40°C~+120°C

Flexibility

Highly flexible

Certificate

CE

Profile



Corugated PVC Conduit

Series Code	ZM.15
Features	Corugated , PVC.
Product Photo	

Item Code (Grey)	Nom. Size	ID (mm)	OD (mm)	Packed (m)
ZM.15.1001	8	8	12	30
ZM.15.1002	10	10	14,5	30
ZM.15.1003	12	12	16,3	30
ZM.15.1004	14	14	18,6	30
ZM.15.1005	16	16	20,5	30
ZM.15.1006	20	20	24,7	30
ZM.15.1007	22	22	27	30
ZM.15.1008	25	25	30,3	30
ZM.15.1009	28	28	33,2	30
ZM.15.1010	30	30	36	30
ZM.15.1011	32	32	37,5	30
ZM.15.1012	35	35	40,5	30
ZM.15.1013	38	38	44,1	30
ZM.15.1014	40	40	46,2	30
ZM.15.1015	45	45	51,8	30
ZM.15.1016	50	50	57	30

Temperature
Range

-
40°C ~ +120
°C

Flexibility

Highly flexible

Certificate

CE

Profile



Polyamide Capped Strap

Series Code	ZM.16
Features	Polyamide (PA6) Straight, halogen-free.
Temperature Range	-40 °C +120 °C
IP Rating	IP67
Material Certificate	Polyamide (PA6) CE
Product Photo	

Item Code (Black)	Item Code (Grey)	Suitable Flex. Cond.Type
ZM.16.7001	ZM.16.1401	PA/PP 7
ZM.16.7002	ZM.16.1402	PA/PP 8
ZM.16.7003	ZM.16.1403	PA/PP 9
ZM.16.7004	ZM.16.1404	PA/PP 11
ZM.16.7005	ZM.16.1405	PA/PP 13
ZM.16.7006	ZM.16.1406	PA/PP 16
ZM.16.7007	ZM.16.1407	PA/PP 22
ZM.16.7008	ZM.16.1408	PA/PP 29
ZM.16.7009	ZM.16.1409	PA/PP 36
ZM.16.7010	ZM.16.1410	PA/PP 48