

Insulated Flexible Steel Conduit / Water-proof

SeriesCode | ZM.02

Features | Square-lock, Galvanized Steel, PVC Coated (Black)



Item Code	SIZE (METRIC)	Nom. Size	Us T. Size	ID (mm)	OD (mm)	Bed.Rad. (mm)
ZM.02.3010	12	11	1/4"	10.0	14.0	40.0
ZM.02.3013	16	14	3/8"	13.0	17.0	45.0
ZM.02.3016	20	16	1/2"	16.0	21.0	70.0
ZM.02.3021	25	21	3/4"	21.0	26.0	70.0
ZM.02.3026	32	26	1"	26.0	32.0	95.0
ZM.02.3035	40	35	1 1/4"	35.0	41.0	110.0
ZM.02.3040	50	40	1 1/2"	40.0	47.0	120.0
ZM.02.3050	63	50	2"	52.0	59.0	180.0

Temperature Range | -25°C~+90°C

IP Rating | IP 54-IP 66

Flexibility | High

Certificate | CE

Fire Retardant | Self-extinguishing

UV Resistance | By ordering



Temperature Range | -25°C~+90°C

IP Rating | IP 54-IP 66

Flexibility | High

Certificate | CE

Fire Retardant | Self-extinguishing

UV Resistance | By ordering

