

## PVC TRUNKING


<b>Material</b>	: Rigid PVC
<b>Certificate</b>	: CE( Test Standard : EN50085 ) ; RoHS
<b>Flammability Rating</b>	: FV -O ; FH -1
<b>Struction</b>	: Duct Bottom and Cover
<b>Application</b>	: Used in Electric apparatus, Stage
<b>Work Temperature</b>	: -40 C - 65 C
<b>Color</b>	: Ivory , Snow White , Bluish White.



### Features

1. Non - Conductive : high insulation, resist up to 25 KV (Voltage), assuring a safe system.
2. Solid design - Anti-Dust and Anti-Mouse
3. High Tenacity Strength, Combustion, Fire and Damp proof, Resistant to Ageing and Alkalescency.
4. Easy Installation : Light weight, easy to cut, bend , handle and transport.
5. Mini Trunking has been designed to be used in both the square and cornered surface mounted Switch and Socket boxes.

**Note** : Trunking can be provided - Plain ( Non-Adhesive )  
 - Adhesive  
 - With Mounting Holes



## PVC TRUNKING - ADHESIVE

MODEL NO.	SIZE	THICKNESS
SNTA 1010	10X10X2900MM	0.60 MM Sticker width: 7MM
SNTA 1616	16X16X2900MM	0.90 MM Sticker width: 13MM
SNTA 2516	25X16X2900MM	0.90 MM Sticker width: 22MM
SNTA 3825	38X25X2900MM	1.00 MM Sticker width: 35MM



## PVC TRUNKING - NON- ADHESIVE

MODEL NO.	SIZE	THICKNESS
SNT 1616	16X16X2900MM	T: 0.90 MM
SNT 2516	25X16X2900MM	T: 0.90 MM
SNT 3825	38X25X2900MM	T: 1.0 MM
SNT 5050	50X50X2900MM	T: 1.50 MM
SNT 7550	75X50X2900MM	T: 1.50 MM
SNT 7575	75X75X2900MM	T: 1.50 MM
SNT 10050	100X50X2900MM	T: 1.65 MM
SNT 100100	100X100X2900MM	T: 2.0 MM



## PVC ARC TRUNKING- ADHESIVE

MODEL NO.	SIZE	THICKNESS
SNART 1035	10X35X2000MM	Cover : 1.30mm Base : 1.10mm Sticker width: 18mm
SNART 1448	14X48X2000MM	Cover : 1.30mm Base : 1.20mm Sticker width: 30mm
SNART 1665	16X65X2000MM	Cover : 2.20mm Base : 1.60mm Sticker width: 40mm
SNART 25100	25X100X2000MM	Cover : 1.90mm Base : 1.70mm Sticker width: 80mm

