

PLASTIC ENCLOSURE

REFERENCE STANDARD: IEC 60670

- MADE OF SELF EXTINGUISHING ENGINEERING PLASTIC.
- RAL 7035 GREY
- MAX OPERATION TEMPERATURE: -25°C - +85°C.
- INSULATION COMPLIES TO EN 60439-1.



BOX WITH CABLE SLEEVES – IP56 – WITH SCREW – DOWN COVER

INTERNAL DIMENSIONS (AXBXh)mm	FASTENING SCREWS
100 X 100 X 50	4
120 X 80 X 50	4
150 X 110 X 70 (.) Δ	4
150 X 150 X 70 (.) Δ	4
150 X 150 X 80 (.) Δ	4
190 X 140 X 70 (.) Δ	4
240 X 240 X 80 (.) Δ	4
240 X 190 X 90 (.) Δ	4
300 X 200 X 120 (.) Δ	4
380 X 300 X 120 (.) Δ	4
460 X 380 X 130 (.) Δ	6

- (.) - Optional Wall mounting brackets
 Δ - Suitable for hinges mounting.

HIGHER BOX WITH CABLE SLEEVE – IP56 – SCREW- DOWN COVER

INTERNAL DIMENSIONS (AXBXh)mm	FASTENING SCREWS
100 X 100 X 80	4
240 X 190 X 125	4
300 X 220 X 170	4
380 X 300 X 170 (.)Δ	4
460 X 380 X 130 (.)Δ	6

- (.) - Optional Wall mounting brackets
 Δ - Suitable for hinges mounting.

