

# WIRING DEVICES & ACCESSORIES

## SWITCH SOCKETS



SN 405



SN 406



SN 407



SN 480



SN 429


MODEL NO.	MODEL	AMPERE RATING (A)	POWER (W)	STANDARD	MEASUREMENT / UNIT	CTN PACKING
SN 405	13A 1 GANG SWITCHED SOCKET	13	3250 W	BS 1363	86 X 86 MM	100 NOS/ CARTON
SN 406	13A 2 GANG SWITCHED SOCKET	13	3250 W	BS 1363	86 X 146 MM	50 NOS/ CARTON
SN 407	13A 1 GANG SWITCHED SOCKET WITH NEON	13	3250 W	BS 1363	86 X 86 MM	100 NOS/ CARTON
SN 480	13A 1 GANG MULTI - FUNCTION SWITCHED SOCKET	13	3250 W	BS 1363	86 X 86 MM	100 NOS/ CARTON
SN 429	15A 1 GANG SWITCHED SOCKET	15	3750 W	BS 1363	86 X 86 MM	100 NOS/ CARTON

APPLICABLE WIRE RANGES	L,N,E
FOR 13 A SOCKETS	2.5 mm <sup>2</sup> - 6.0 mm <sup>2</sup>
FOR 15 A SOCKETS	2.5 mm <sup>2</sup> - 6.0 mm <sup>2</sup>


INSULATION STRIPPING GAUGE	L,N	E
FOR 13 A SOCKETS	10	10
FOR 15 A SOCKETS	10	10

APPROPRIATE TIGHTENING TORQUE	L,N	E
FOR 13 A SOCKETS	1.6Nm-2.0Nm	1.6Nm-2.0Nm
FOR 15 A SOCKETS	1.6Nm-2.0Nm	1.6Nm-2.0Nm


VOLTAGE RATING	250 V~
MATERIAL	UREA
CONDUCTING STRIP & CLIP	BRASS & COPPER
CONTACTS	SILVER
MOUNTING DEPTH - 13A	18 mm
MOUNTING DEPTH - 15A	24 mm




SN 405 / SN 407



SN 406 TO FUNCTIONAL EARTH



SN 429



SN 480