

NT Low Voltage Fuse

Application

NT low voltage H.R.C. fusw features light in weight, small in size, low in power loss and high in breaking capacity. This product has been widely used in overload and short circuit protection of electric installation. This product conforms to IEC 60269 standards with all of the rating at the world advanced level.

Specification

Type	Fuse link				Fuse Base		
	Rated current (A)	Rated voltage (V)	Rated power loss (W)	Weight (kg)	Type	Rated current (A)	Weight (kg)
NT00C	2	500,600	0.41	0.15	Sist 101	160	0.2
	4		0.62				
	6		0.81				
	10		1.08				
	16		1.60				
	20		1.81				
	25		2.31				
	32		3.07				
	36		3.17				
	40		4.05				
	50		4.25				
	63		4.70				
	80		5.7				
	100		7				
NT00	4	500,600	0.67	0.15	Sist 101	160	0.2
	6		0.89				
	10		1.14				
	16		1.65				
	20		1.94				
	25		2.50				
	32		3.32				
	36		3.56				
	40		4.30				
	50		4.5				
	63		4.6				
	80		6				
	100		7.3				
	125	500	7.6				
	160		9.6				
NT0	6	500,600	1.03	0.2	Sist 160	160	0.32
	10		1.42				
	16		2.45				
	20		2.36				
	25		2.7				
	32		3.74				
	35		4.3				
	40		4.7				
	50		5.5				
	63		6.9				
	80		7.6				
	100		8.9				
	125	500	10.1				
	160		15.2				



NT00C



NT00



NT0